

# Drain: Capac FONTA PIPE BASE cu tub telescop pt tub gofrat D315. H.0,5 m B125 (TT666400)

## TT666400

**315 mm**  
HOSSZ

**500 mm**  
MAGASSÁG

**315 mm**  
SZÉLESSÉG



### FELHASZNÁLÁS:

Covering and closing devices for manholes and drains located in roadways without heavy traffic and pedestrian areas. They can be placed on shoulders, parking lots and parking spaces for all types of road vehicles.

### MINŐSÉGI FELTÉTELEK:

- SR EN 124-2:2015
- EU Regulation No. 305/2011

### ELŐNYÖK:


- Use in industrial areas
- Easy to handle and install
- Long service life
- Balanced ratio between load class and product weight

### ÉLETTARTAM:

- 50 years - subject to compliance with assembly, storage and operation instructions.

## SZERELÉS

Installation and commissioning shall only be carried out in areas compliant with the product's load class. Commissioning shall be carried out by specialized personnel.

-  For efficient installation, we recommend using G12M29-C sealant. It is used for sealing gutters, pipes and drainage systems;
- Curing time: 24h/2-3 mm
  - Temperature resistance: -40° C to +70° C
  - Processing temperature: +5° C to +40° C
- BASE sealing paste (sealant) PP-FB-PB gutters, tube, 310 ml (G12M29-C)



1

**JELLEMZŐK**

<b>Termék neve</b>	Capac FONTA PIPE BASE cu tub telescop pt tub gofrat D315. H.0,5 m B125 (TT666400)
<b>Termékkód</b>	TT666400
<b>EAN kód</b>	6426282033170
<b>Termékkategória</b>	PIPE BASE - Cămine de inspecție
<b>Brand</b>	Drain
<b>Súly</b>	19.00 kg
<b>Termelő</b>	MAGNAPLAST SP.Z.O.O