

# Urban: Capac FONTA URBAN rotund D.800 PL.600 Hext.65 EUROPE cu inchizator B125 (35258-35M)

## 35258-35M

**800 mm**

LENGTH / EXTERIOR DIAMETER

**600 mm**

WIDTH / INTERIOR DIAMETER



### USAGE:

Cast iron covers in this class are used for closing and protecting inspection chambers in sewage networks located on sidewalks, pedestrian areas, similar zones, parking lots, or multi-level parking structures.

### QUALITY CONDITIONS:

- SR EN 124
- EU Regulation No. 305/2011
- Declaration of Conformity

### ADVANTAGES:

- Durability;
- Aesthetic design;
- Balanced ratio between load class and product weight;
- Warranty (2 years)
- Easy to handle

### LIFESPAN:

- 20 years - with adherence to installation, storage, and operation instructions.

## INSTALLATION

Installation and commissioning must only be carried out in areas that comply with the product's load class. Commissioning should be performed by qualified personnel.



For efficient installation, we recommend using the G12M29-C sealant. It is used for sealing gutters, pipes, and drainage systems components:



- Curing time: 24 hours / 2-3 mm
- Temperature resistance: -40°C to +70°C
- Processing temperature: +5°C to +40°C BASE sealing paste (sealant) for PP-FB-PB gutters, tube, 310 ml (G12M29-C)



## CHARACTERISTICS

<b>Product name</b>	Capac FONTA URBAN rotund D.800 PL.600 Hext.65 EUROPE cu inchizator B125 (35258-35M)
<b>Product code</b>	35258-35M
<b>EAN code</b>	6426282034771
<b>Product category</b>	Capace fonta (B125 - F900)
<b>Brand</b>	Urban
<b>Weight</b>	30.00 kg
<b>Stock availability</b>	Stockable
<b>Length, mm</b>	800
<b>Width, mm</b>	800
<b>Height (H), mm</b>	65
<b>Interior diameter / Clear opening (mm)</b>	600
<b>Exterior diameter (mm)</b>	800
<b>Load class</b>	B125
<b>Distributor</b>	VODALAND Balkan SRL
<b>Product Material</b>	Cast Iron
<b>Fastening System</b>	Screw
<b>Colour</b>	Black
<b>Forma</b>	Rotund
<b>Warranty, months</b>	24
<b>Lifespan, years</b>	20
<b>Producer</b>	Hebei Cheng An Babel Casting