



Drain: Sifon INOX STAINLESS 250x250 cu capac fante iesire verticala DN150 R50 250x250x314 (0522.15.11.2)

0522.15.11.2

250 mm

314 mm HEIGHT 250 mm



USAGE:

The stainless steel drain trap is a useful, pragmatic and modern solution and is used to evacuate wastewater and direct it to underground sewer columns.

QUALITY CONDITIONS:

• According to SR EN 1253-1:2015

ADVANTAGES:

- · Easy access for inspection and cleaning
- Easy to clean and disinfect
- Corrosion resistance
- Thermal resistance to detergents and disinfectants
- Use in the food industry
- · Long service life

LIFESPAN:

• 20 years - subject to compliance with assembly, storage and operation instructions.

Pag. 1/3 www.vodaland.ro





INSTALLATION


The commissioning of stainless steel siphons is carried out by specialized personnel, in compliance with the manufacturer's instructions and safety and stability requirements. Stainless steel siphons can also transport other types of industrial wastewater, provided that there is no risk of damage to the components or that they are harmful to health.

For efficient installation, we recommend using G12M29C sealant. It is used for sealing gutters, pipes and drainage systems.



- Curing time: 24h/2-3 mm
- Application temperature: +5° C to +40°C
- Maximum storage temperature: 32°C

BASE sealant, construction products, 310 ml tube (G12M29-C).









Dimensional range:

0521.10.11.2	STAINLESS 200x200 stainless steel drain with slotted cover, vertical outlet DN110 200x200x278 (0521.10.11.2)
0521.10.11.3AS	STAINLESS 200x200 stainless steel drain with anti-slip grid type grate, vertical outlet DN110 200x200x278 (0521.10.11.3AS)
0522.10.11.2	STAINLESS 250x250 stainless steel siphon with slotted cover, vertical outlet DN110 250x250x314 (0522.10.11.2)
0522.15.11.2	STAINLESS 250x250 stainless steel siphon with slotted cover, vertical outlet DN150 250x250x314 (0522.15.11.2)
0522.10.11.3AS	STAINLESS 250x250 stainless steel siphon with anti-slip grid type grate, vertical outlet DN110 250x250x314 (0522.10.11.3AS)
0522.15.11.3AS	STAINLESS 250x250 stainless steel trap with anti-slip grid type grate, vertical outlet DN150 250x250x314 (0522.15.11.3AS)
0523.15.11.3AS	STAINLESS 300x300 stainless steel drain with anti-slip grid type grate, vertical outlet DN150 300x300x344 (0523.15.11.3AS)
0523.15.11.2	STAINLESS 300x300 siphon with slotted cover, vertical outlet DN150 300x300x344 (0523.15.11.2)

Pag. 2/3 www.vodaland.ro





CHARACTERISTICS		
Product name		
Product code	0522.15.11.2	
EAN code	6427669001614	
Product cathegory	Sifoane pardoseală din inox	
Brand	Drain	
Weight	6.41 kg	
Stock availability	On order	
Length, mm	250	
Width, mm	250	
Height (H), mm	314	
Pipe connection (DN)	150	
Load class	R50	
Product Material	Inox	
Grate fastening system	Click	
Warranty, months	24	
Lifespan, years	20	
Producer	VODALAND INDUSTRY LLC	

Pag. 3/3 www.vodaland.ro