

# Urban: Capac FONTA URBAN rotund D.810 PL.600 Hext.80 cu inchizator C250 (816080C)

## 816080C

**810 mm**

HOSSZ / KÜLSŐ ÁTMÉRŐ

**600 mm**

SZÉLESSÉG / BELSŐ ÁTMÉRŐ



### FELHASZNÁLÁS:

Cast Iron Covers in this class are used to close and protect manholes used in sewer networks located in public traffic areas, parking lots and on road surfaces, near sidewalk curbs and in non-traffic areas, without shoulders.

### MINŐSÉGI FELTÉTELEK:

- SR EN 124-6
- EU Regulation No. 305/2011

### ELŐNYÖK:


- Durability;
- Aesthetic design;
- Balanced ratio between load class and product weight;
- Warranty (2 years)
- Easy to handle

### TERMÉKGARANCIA:

- 20 years - subject to compliance with assembly, storage and operation instructions.

## SZERELÉS

Installation and commissioning shall only be carried out in areas compliant with the product's load class. Commissioning shall be carried out by specialized personnel.

 For efficient installation, we recommend using the Standart Park G12M29-C sealant.

It is used for sealing gutters, pipes and drainage systems;

- Curing time: 24h/2-3 mm
- Temperature resistance: -40° C to +70° C
- Processing temperature: +5° C to +40° C

- BASIC sealing paste (sealant) PP-FB-PB gutters, tube, 310 ml (G12M29-C)



## JELLEMZŐK

<b>Termék neve</b>	Capac FONTA URBAN rotund D.810 PL.600 Hext.80 cu inchizator C250 (816080C)
<b>Termékkód</b>	816080C
<b>EAN kód</b>	6427669001201
<b>Termékkategória</b>	Capace fonta (B125 - F900)
<b>Brand</b>	Urban
<b>Súly</b>	38.00 kg
<b>Készlet elérhetősége</b>	Tárolható
<b>Hossz, mm</b>	810
<b>Szélesség, mm</b>	810
<b>Magasság (M), mm</b>	80
<b>Belső átmérő / hézag (mm)</b>	600
<b>Külső átmérő (mm)</b>	810
<b>Terhességi osztály</b>	C250
<b>Elosztó</b>	VODALAND Balkan SRL
<b>Termék anyaga</b>	Öntöttvas
<b>Rögzítőrendszer</b>	
<b>Szín</b>	Fekete
<b>Forma</b>	Kerek
<b>Garancia, hónap</b>	24
<b>Termelő</b>	SEÇ METALURJI