




Urban: Capac OZ URBAN UNIFILL ASCUNS patrat 690x690 PL.600x600 Hext.100 Hin.60 cu inchizator B125 (30416.10-3)

30416.10-3

690 mm LENGTH / EXTERIOR DIAMETER 690 mm width / interior diameter



USAGE:

The Galvanized Steel Cover of this class is used to close and protect manholes used in sewer networks located on sidewalks, pedestrian areas and similar areas, parking lots or multi-storey car parks.

QUALITY CONDITIONS:

- SR EN 124-6
- EU Regulation No. 305/2011

ADVANTAGES:

- Durability;
- Aesthetic design;
- Balanced ratio between load class and product weight;
- Warranty (2 years)
- · Easy to handle

LIFESPAN:

• 20 years - subject to compliance with assembly, storage and operation instructions.

Pag. 1/3 www.vodaland.ro





INSTALLATION

Installation and commissioning shall only be carried out in areas compliant with the product's load class. Commissioning shall be carried out by specialized personnel. For efficient installation, we recommend using G12M29-C sealant.

It is used for sealing gutters, pipes and drainage systems;

- Curing time: 24h/2-3 mm

- Temperature resistance: -40° C to +70° C - Processing temperature: +5° C to +40° C

• BASE sealing paste (sealant) PP-FB-PB gutters, tube, 310 ml (G12M29-C)









Pag. 2/3 www.vodaland.ro





CHARACTERISTICS

CHARACTERISTICS	
Product name	
Product code	30416.10-3
EAN code	6427669002000
Product cathegory	Capace ascunse otel zincat (B125)
Brand	Urban
Weight	23.22 kg
Stock availability	On order
Length, mm	690
Width, mm	690
Height (H), mm	100
Interior diameter / Clear opening (mm)	600x600
Load class	B125
Product Material	Galvanized Steel
Fastening System	
Warranty, months	24
Lifespan, years	20
Producer	VODALAND INDUSTRY LLC

Pag. 3/3 www.vodaland.ro