



Drain: Kit rigola FB BASE LN100 Hext.125 gratar OZ grila antitoc A15 1000x140x125 (040002020)

040002020

1000 mm LENGTH 130 mm

HEIGHT

140 mm WIDTH



USAGE:

Sidewalks, pedestrian areas and similar areas, parking lots or multi-storey car parks.

QUALITY CONDITIONS:

- According to SR EN 1433:2002
- According to EU Regulation No. 305/2011
- Declaration of Performance

ADVANTAGES:

- Easy to handle and install
- UV-resistant
- · Various installation widths and heights
- Use in residential areas or private homes
- · Long service life

LIFESPAN:

• 20 years - subject to compliance with assembly, storage and operation instructions


Pag. 1/3 www.vodaland.ro





INSTALLATION

The Base gutter drainage system can be installed without a collector chamber because both ends of the gutter can be closed with end pieces, and the discharge point to the sewer network will be made through the vertical connection of the gutter.



It is used for sealing gutters, pipes and drainage systems.

- Curing time: 24h/2-3 mm
- Operating temperature: -10° C to +40° C
- Storage conditions: Store in a ventilated area, at low temperatures.

BASE sealant, construction products, 310 ml tube (G12M29-C).





Conexiune tronson Conexiune tronson









Etansant BASE, produse pentru constructii, tub 310 ml (G12M29-C)



Placa capat PB BASE cu stut pt rigola FB LN100 Hext.125 (6701-09B)



Placa capat PB BASE pt rigola FB LN100 Hext.125 140x106 (6701-B)

Pag. 2/3 www.vodaland.ro





CHARACTERISTICS	
Product name	
Product code	040002020
EAN code	6427669010487
Product cathegory	Rigole beton BASE (A15-C250)
Brand	Drain
Weight	25.40 kg
Stock availability	On order
Length, mm	1000
Exterior width, mm	140
Nominal Length, mm	LN100
Exterior Height, mm (Hext)	130
Interior Height, mm (Hint)	125
Load class	B125
Channel material	Concrete
Grate Material	Galvanized Steel
Grate fastening system	Fastener
Warranty, months	24
Lifespan, years	20
Producer	BETONIKA

Pag. 3/3 www.vodaland.ro