

# Urban: Capac OZ URBAN UNIFILL ASCUNS patrat 680x680 PL.600x600 Hext.80 Hin.40 cu inchizator B125 (5000.2897)

## 5000.2897

**680 mm**  
HOSSZ / KÜLSŐ ÁTMÉRŐ

**680 mm**  
SZÉLESSÉG / BELSŐ ÁTMÉRŐ



### FELHASZNÁLÁS:

The Galvanized Steel Cover of this class is used to close and protect manholes used in sewer networks located on sidewalks, pedestrian areas and similar areas, parking lots or multi-storey car parks.

### MINŐSÉGI FELTÉTELEK:

- SR EN 124-6
- EU Regulation No. 305/2011

### ELŐNYÖK:


- Durability;
- Aesthetic design;
- Balanced ratio between load class and product weight;
- Warranty (2 years)
- Easy to handle

### ÉLETTARTAM:

- 20 years - subject to compliance with assembly, storage and operation instructions.

## SZERELÉS

Installation and commissioning shall only be carried out in areas compliant with the product's load class. Commissioning shall be carried out by specialized personnel.

 For efficient installation, we recommend using G12M29-C sealant.

It is used for sealing gutters, pipes and drainage systems;

- Curing time: 24h/2-3 mm
- Temperature resistance: -40° C to +70° C
- Processing temperature: +5° C to +40° C

- BASE sealing paste (sealant) PP-FB-PB gutters, tube, 310 ml (G12M29-C)



## JELLEMZŐK

<b>Termék neve</b>	Capac OZ URBAN UNIFILL ASCUNS patrat 680x680 PL.600x600 Hext.80 Hin.40 cu inchizator B125 (5000.2897)
<b>Termékkód</b>	5000.2897
<b>EAN kód</b>	6426282034184
<b>Termékkategória</b>	Capace ascunse otel zincat (B125)
<b>Brand</b>	Urban
<b>Súly</b>	18.00 kg
<b>Készlet elérhetősége</b>	Tárolható
<b>Hossz, mm</b>	680
<b>Szélesség, mm</b>	680
<b>Magasság (M), mm</b>	80
<b>Belső átmérő / hézag (mm)</b>	600x600
<b>Terhességi osztály</b>	B125
<b>Termék anyaga</b>	Horganyzott acél
<b>Rögzítőrendszer</b>	surub
<b>Garancia, hónap</b>	24
<b>Élettartam, évek</b>	20
<b>Termelő</b>	VODALAND INDUSTRY LLC