## DECLARATION OF PERFORMANCE

No.RI-22.08.284


## According to EU Regulation No. 305/2011

- 1. Unique identification code: SHOB1-1LS
- 2. Product Type: Separatoare Hidrocarburi OilBase fara by-pass
- **3.** Usage: Dimensional range: Hydrocarbon separators made of glass fiber reinforced polyester with nominal flow rates from 1 l/s to 50l/s without bypass. Light liquid separators protect the groundwater from hydrocarbons generated by car traffic. Applications: Underground and above-ground parking lots, gas stations, logistics parks.
- 4. Manufacturer: FIBERICA
- **5.** Authorized representative: Vodaland Balkan SRL
- **6.** System for the Assessment and Verification of Constancy of Performance: System 3
- 7. Harmonized Standard: SR EN 858
- **8.** Declared Performance:

Characteristics	Declared performance	Harmonized technical specifications
Reaction to fire class	Е	SR EN 858
Liquid tightness	No water leaks or leaks were observed	SR EN 858
Effectiveness	Fulfilled*	SR EN 858
Resistance under load	147,4 kN	SR EN 858
Tensile strenght	10,29 MPa	SR EN 858

<sup>\*</sup>Average efficiency of the prototype product tested = 1,456 mg/l

**9.** The performance of the product identified at points 1 and 2 complies with the performance specified at point 8. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified at point 4. **Signed on behalf of the manufacturer by:** 



<sup>\*</sup> The reference number of the type test document is available upon request.