



Channel with Grate E600 Channel with Grate E600 and vertical outlet 110



Article	H/h, mm	Weight kg	Article	H/h, mm	Weight kg	Article	H/h, mm	Weight kg	Article	H/h, mm	Weight kg
04100/230	230	68,4	04100/230-225	230/225	67,9	0410009/230	230	67,3	0410009/230-225	230/225	66,8
04100/225	225	67,5	04100/225-220	225/220	67,0	0410009/225	225	66,4	0410009/225-220	225/220	65,9
04100/220	220	66,5	04100/220-215	220/215	66,1	0410009/220	220	65,4	0410009/220-215	220/215	65,0
04100/215	215	65,6	04100/215-210	215/210	65,2	0410009/215	215	64,5	0410009/215-210	215/210	64,1
04100/210	210	64,7	04100/210-205	210/205	64,3	0410009/210	210	63,6	0410009/210-205	210/205	63,2
04100/205	205	63,8	04100/205-200	205/200	63,3	0410009/205	205	62,7	0410009/205-200	205/200	62,2
04100/200	200	62,9	04100/200-195	200/195	62,4	0410009/200	200	61,8	0410009/200-195	200/195	61,3
04100/195	195	61,9	04100/195-190	195/190	61,5	0410009/195	195	60,8	0410009/195-190	195/190	60,4
04100/190	190	61,0	04100/190-185	190/185	60,6	0410009/190	190	59,9	0410009/190-185	190/185	59,5
04100/185	185	60,1	04100/185-180	185/180	59,7	0410009/185	185	59,0	0410009/185-180	185/180	58,6
04100/180	180	59,2	04100/180-175	180/175	58,7	0410009/180	180	58,1	0410009/180-175	180/175	57,6
04100/175	175	58,2	04100/175-170	175/170	57,8	0410009/175	175	57,1	0410009/175-170	175/170	56,7
04100/170	170	57,3	04100/170-165	170/165	56,9	0410009/170	170	56,2	0410009/170-165	170/165	55,8
04100/165	165	56,4	04100/165-160	165/160	55,9	0410009/165	165	55,3	0410009/165-160	165/160	54,8
04100/160	160	55,4	04100/160-155	160/155	55,0	0410009/160	160	54,3	0410009/160-155	160/155	53,9
04100/155	155	54,5	04100/155-150	155/150	54,0	0410009/155	155	53,4	0410009/155-150	155/150	52,9
04100/150	150	53,5	04100/150-145	150/145	53,1	0410009/150	150	52,4	0410009/150-145	150/145	52,0
04100/145	145	52,6	04100/145-140	145/140	52,2	0410009/145	145	51,5	0410009/145-140	145/140	51,1
04100/140	140	51,7	04100/140-135	140/135	51,2	0410009/140	140	50,6	0410009/140-135	140/135	50,1
04100/135	135	50,7	04100/135-130	135/130	50,3	0410009/135	135	49,6	0410009/135-130	135/130	49,2
04100/130	130	49,8				0410009/130	130	48,7			

1. Dimensions for reference
2. Delivery and packaging are carried out in accordance with the terms of the contract
3. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
4. Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:		DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION	
						TITLE: Concrete Drain Channel Mega DN110 H130-230 with Cast Iron Grate E600			
DRAWN		SIGNATURE		DATE		MATERIAL:		ARTICLE:	
O. Kozhukh				03.10.2022		Concrete, Cast Iron		A3	
CHK'D		SIGNATURE		DATE		WEIGHT: kg		SCALE:1:5	
V. Kyselytsia								SHEET 1 OF 1	
APPV'D		SIGNATURE		DATE					
I. Malynovskiy									
MFG		SIGNATURE		DATE					