


1. \*Template for connecting a channel with a height of 260 mm
2. Dimensions for reference
3. Delivery and packaging are carried out in accordance with the terms of the contract
4. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
5. Deviation of the actual weight of the nominal can be up to 10%.

Nb	Article	Name	Weight, kg
1	042871334	Concrete Sand Trap Pro DN150 H500 with Cast Iron Grate D400	67.3
2	042871334-K	Concrete Sand Trap Pro DN150 H500 with basket with Cast Iron Grate D400	69
3	042871334-P160	Concrete Sand Trap Pro DN150 H500 outlet 160 with Cast Iron Grate D400	66.3
4	042871334-P160-K	Concrete Sand Trap Pro DN150 H500 with basket outlet 160 with Cast Iron Grate D400	68

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN Kyselytsia		SIGNATURE	DATE 13.09.22	 TITLE: <b>Concrete Sand Trap Pro DN150 H500 with Cast Iron Grate D400</b>	
CHK'D Kharambura					
APPV'D Malynovskiy					
MFG					
Q.A		MATERIAL: Concrete, Cast Iron		ARTICLE: 042871334	A3
		WEIGHT: kg		SCALE: 1:5	SHEET 1 OF 1