



1. Template for connecting a channel with a height of 310 mm
2. The sand trap has two sockets for a 200 mm pipe
3. Dimensions for reference
4. Delivery and packaging are carried out in accordance with the terms of the contract
5. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
6. Deviation of the actual weight of the nominal can be up to 10%.

No	Article	Name	Weight kg
1	045871334-P200	Concrete Sand Trap Pro DN200 H600 outlet 200 with Cast Iron Grate D400	82,8
2	045871334-P200-K	Concrete Sand Trap Pro DN200 H600 outlet 200 with Basket with Cast Iron Grate D400	85,6

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A-01	
SURFACE FINISH:								<b>Concrete Sand Trap Pro DN200 H600 outlet 200 with Cast Iron Grate D400</b>	
TOLERANCES: ISO 2768 - C									
LINEAR:						MATERIAL: Concrete, Cast Iron			
ANGULAR:						WEIGHT: kg		SCALE: 1:5	
DRAWN: Kyselytsia		SIGNATURE:		DATE: 13.09.22				SHEET 1 OF 1	
CHK'D: Kharambura									
APPV'D: Malynovskiy									
MFG:									
Q.A:									