Grease Separator Vodaland GBase-15 with sludge trap (\$1:30) A -Manhole design * Detail A.1- Traffic zone C.1 Detail A Ø620 \MS sealant Detail B Ø1000 Detail A.2-Pedestrain zone C.1 3.2 C.3 MS sealant (D) 0 Detail A .3- Grass zone Ø620/800 (D) D=2400 Ø2600 B-Fixing the manhole with the A - AManhole MS sealant Body C -Pipes location D1- inlet / D2- outlet on plan 1 = G 25° D=2400 Ø2600

- *H-depth of the inlet connection, mm (in standard equipment H up to 2000 mm). H take a multiple of 50mm. When filling the manhole A.1 – the overall height of the product is less than 200mm; at the design of the manhole A.2 – the total height of the product is bigger than 100 mm.
- ** The product is shipped in accordance with the Standard equipment (Tabl. 1), unless otherwise specified in the Additional equipment (Tabl. 2). The complete set of the product agrees with the manager.
- ***The manufacturer has the right to make constructive and pattern changes that do not worsen the characteristics of the product as a whole

Permissible deviation during production of products is 1-3%.

Additional equipment:_

Specification of materials and equipment. Standard equipment ** (Tabl. 1)

Pos.	Identification	Name	Q-ty	Mass pc., kg	Note
1	Vodaland	Grease Separator Vodaland GreaseBase- 15 with sludge trap, fiberglass disch. 15 l/s , D=2400 Hk=2130	1	945	compl.
2		Inspection manhole Ø 1000x620	1		compl.
3.1	D1-Inlet pipe	Rubber seal for connection PVC SN4 Ø 200	1		compl.
3.2	D2-Outlet pipe	Rubber seal for connection PVC SN4 Ø 201	1		compl.
		Volume of light liquids	1690		l
		Volume of sludge trap	1590		l

** The product is shipped in accordance with the Standard equipment (Tabl. 1), unless otherwise specified in the Additional equipment (Tabl. 2)

Additional equipment (Tabl. 2)

Pos.			lde	וח≘	tificatio	П		Name			Note		
A , B								D1-Inlet pipe / D2-Outlet pipe :	folget 1	Outlet G			
	For connection D1, D2:						71, D2:	Funnel					
								Smooth end					
								Another:					
				Dia	ameter D	pipes D	11, D2:	ø90					
								Ø160					
								Another:					
С		Manhole design (see A.1, A.2)											
		C.1 Cover:						Garden plastic					
								Load class A 15					
								Load class C 250		V			
		C.2						Load class D400					
							<i>C.2</i>	Fiberglass cover Ø620					
		C.3 Fiberglass adaptor plate					plate	Ø620, h=200mm		V			
								Another:					
D		D. Universal ladder						Aluminium					
								s/s	[
Ε		E. Level sensor						Oil	[A A		
								Sludge					
F		F. Fastening				F. Fasi	ening	Belt fastening for D 2400					
			+				-						
Chan.	Q-1	ty Sher	† №d	or.	Signature	Date	ł						
enam.		7 07720	, ,, ,,	0 07		2070				Phase	Sheet	Sheets	
							<u> </u>		_				
	Gre						- Gr	rease Separator Vodaland GBase- (GB-15)	15		VODA	ALAND	