Grease Separator Vodaland GBase- 7 with sludge trap (\$1:25) A -Manhole design * Detail A Detail A.1- Traffic zone C.1 Ø620 MS sealant Ø800 Detail B Detail A.2-Pedestrain zone C.1 D1 MS sealant *3.2* (D) 0 Detail A .3- Grass zone (C.2) 1100 (D) B-Fixing the manhole with the body *** D=1800 <u>z</u>5 Detail B Ø2000 Manhole A - AMS sealant Body 3.2 C-Pipes location D1- inlet / D2- outlet on plan <u>3.1</u> G ?25° D=1800 Ø2000 *H-depth of the inlet connection, mm (in standard equipment H up to 2000 mm). H take a multiple of 50mm. When filling the manhole A.1 – the overall height of the product is less than 200mm; at the design of the manhole A.2 – the total height of the product is bigger than 100 mm. ** The product is shipped in accordance with the Standard equipment (Tabl. 1), unless otherwise specified in the Additional equipment

***The manufacturer has the right to make constructive and pattern changes that do not worsen the characteristics of the

(Tabl. 2). The complete set of the product agrees with the manager.

Permissible deviation during production of products is 1–3%.

product as a whole

Additional equipment:

Specification of materials and equipment. Standard equipment ** (Tabl. 1)

Pos.	Identification	Name	Q-ty	Mass pc., kg	Note
1	Vodaland	Grease Separator Vodaland GreaseBase- 7 with sludge trap, fiberglass disch. 7l/s, D=1800 H k=1880	1	340	compl.
2		Inspection manhole Ø 800x620	1		compl.
3.1	D1-Inlet pipe	Rubber seal for connection PVC SN4 Ø 160	1		compl.
3.2	D2-Outlet pipe	Rubber seal for connection PVC SN4 Ø 160	1		compl.
		Volume of light liquids	740		l
		Volume of sludge trap	760		l

**The product is shipped in accordance with the Standard equipment (Tabl. 1), unless otherwise specified in the Additional equipment (Tabl. 2)

Additional equipment (Tabl. 2)

Pos.			lden	tificatio	Π		Name	Note			
Α,Β							D1-Inlet pipe / D2-Outlet pipe :		Gutlet B		
	For connection D1, D2:				1, D2:	Funnel					
							Smooth end				
							Another:				
			Di	ameter D	pipes D	1, D2:	Ø90				
							Ø160				
							Another:				
C	Manhole design (see A.1, A								, A .21		
		C.1 Cover:					Garden plastic				
							Load class A 15				
							Load class C 250		V		
							Load class D400				
		C.2				C.2	Fiberglass cover Ø620				
		C.3 Fiberglass adaptor plate				plate	Ø620, h=200мм	\overline{V}			
							Another:				
D		D. Universal ladder				adder	Aluminium			F	
							s/s				
Ε		E. Level sensor				епѕог	Oil			A A	
							Sludge				
F					F. Fast	ening	Belt fastening for D 1800				
Chan. C	Q-ty	Sheet	Nºdoc	Signature	Date						
5									Phase	Sheet	Sheets
						Gi	rease Separator Vodaland GBase- (GB-7)	7	**	VODA	ALANE