Grease Separator with a sludge double trap GPro-7 (\$1:25) A -Manhole design * Detail A Detail A.1- Traffic zone C.1 Ø620 Ø800 MS sealant Detail B Detail A.2-Pedestrain zone C.1 3.1 MS sealant Outlet (D) Detail A.3- Grass zone (C.2) D=2000 B-Fixing the manhole with the Ø2200 body *** A - ADetail B Manhole MS sealant Body C-Pipes location D1-inlet / D2-outlet on plan 10 <u>3.1</u> Inlet 180° *H-depth of the inlet connection, mm (in standard equipment H up to 2000 mm). H take a multiple of 50mm. When filling the manhole A.1 – the overall height of the product is less than 200mm; at the design of the manhole A.2 – the total height of the product is bigger than 100 mm. ** The product is shipped in accordance with the Standard equipment (Tabl. 1), nless otherwise specified in the Additional equipment (Tabl. 2). The complete set of the product agrees with the manager. *** The manufacturer has the right to make constructive and pattern changes that do not worsen the characteristics of the product as a whole Permissible deviation during production of products is 1-3%. Additional equipment:

Specification of materials and equipment Standard equipment ** (Tabl. 1)

Pos.	Identification	Name	Q-ty	Mass.pc .kg	Note
1	Vodaland	Grease Separator Vodaland GreasePro- 7 with a sludge double trap, disch 7l/s, fiberglass D=2000 Ηκ=1850 мм	1	400	compl.
2		Inspection manhole Ø 800 x 620	1		compl.
3.1	D1-Inlet pipe	Rubber seal for connection PVC SN4 Ø 160	1		compl.
3.2	D2-Outlet pipe	Rubber seal for connection PVC SN4 Ø 160	1		compl.
		Volume of light liquids	555		l
		Volume of sludge trap	1041		l

** The product is shipped in accordance with the Standard equipment (Tabl. 1), nless otherwise specified in the Additional equipment (Tabl. 2)

Additional equipment (Tabl. 2)

Pos.	,	Identification Name								Note		
Α, Β								D1-Inlet pipe / D2-Outlet pipe :	Inlet 1	Outlet B		
	For connection D1, D2:				For connec	1, D2:	Funnel					
								Smooth end				
								Another:				
				L	Diametr D	pipes D	1, D2:	Ø90				
								Ø160				
								Another:				
C							<u>Manhole design</u> (s			, A .2)		
		C.1 Cover:					over:	Garden plastic				
								Load class A 15				
								Load class C 250		V		
								Load class D400				
		C.2					C.2	Fiberglass cover Ø620				
		C.3 Fiberglass adaptor plate					plate	Ø620, h=200mm		V		
								Another:				
D		D. Universal ladder				ersal l	adder	Aluminium				
								s/s				
Ε		E. Level sensor					епѕог	Oil			A A	
								Sludge				
F	\square	F. Fastening				F. Fast	ening	Belt fastening for D 2000				
\vdash												
Chan.	Q-	tv	Sheet	№doc	Signature	Date						
chan.	<u> </u>	.,	SHEET	77 000.		Dare				Phase	Sheet	Sheets
									\rightarrow			
		Gre				Grease Separator GPro-7 (GP-7)	⇔ vodaLAND					